



WUCK

- ▶ Duct diffuser for spiral duct
- ▶ Supply
- ▶ double deflection

Design:

Wall diffuser

frame
and vanes: steel
finish: sendzimir

Volume damper

frame
and vanes: steel
finish: black

Available types:

W U - K - O

W duct diffuser
U universal application

- **vanes**

C horizontal and vertical vanes

K frame 24 mm

- **accessories**

O none

V volume damper

S deflectrol / volume damper

O not applicable

Application:

Duct diffuser types WUCK are suitable for the supply of cooled and heated air with a slight temperature difference. The diffuser is suitable for mounting into spiral ductwork. The horizontal and/or vertical vanes are manually adjustable.

Features:

Max. air exchange: up to 8x
Under temperature: up to 10 K
Over temperature: up to 15 K
Free area: 70%

Dimensional data:

Height	Width							
	215	315	415	515	615	815		
65	•	•	•	•	•	•		
115	•	•	•	•	•	•		
215	•	•	•	•	•	•		

Only the sizes in the table are available.

Duct diameter:

Height	Duct diameter min - max
65	150 - 400
115	300 - 900
215	600 - 2400

Remarks:

The stated dimensions are sizes in mm (hole or duct size).
The actual width is W-5 mm.
The actual height is H-5 mm.

Dimensions:



